

SPEZIALA ®

SPEZIALA ® tennis lines represent a sensible advance in traditional tennis lines tapes.

Due to semicircular lateral recesses the hard PVC is made flexible and rollable. A further special characteristic is the fact that the line is tightened with an especially constructed tensioner. The combination of the mentioned details results in many clear advantages.

Meanwhile, numerous clubs and court constructors have made use of these improvements.

- Stability of direction due to pre-tightening.
- Extraordinary ground adhesion due to transverse silt.
- Marked profile leads to an improved gearing between line and tennis ground.
- Upright line-ends are avoided by especially developed, 20cm long end fixers.
- Time-saving installation with only one person.
- Solid profiled steel tube plugs ensure long-lasting durability.
- Fixing of the line with high-grade steel tubular anchor pegs.

Tensile and impact strength tested by the Technical University of Berlin.

Instructions:

1. Measure the court and mark the corner points.
2. About 6cm (2½ inches) in front of the appropriate corner point, hammer the tubular steel profile plugs into the ground. Ensure that the top of the plug is above the surface of the court. Start with the plugs for side lines and the base lines.
3. Start by laying the base lines such that there is a slit above the opening of the plug. Put in the end fixer. Hammer a tubular anchor peg through the line slit into the plug.
4. Straighten the line. Fix the tensioner on the opposite side outside the court.
5. Hook the line in the tensioner and tighten it. Do not overstretch the line! In any case, tighten the line such that a line slit is over the opening of the plug. Put in the end fixer. Hammer the second tubular anchor peg in.
6. Untension SPEZIALA ® and press it into the ground using the line stamper.
7. Cut the end of the line to the correct length using a small hand saw.
8. Lay the other line sections in the same way.

Package contains:

- 4 24m rolls = sidelines
- 1 22m roll = 2 x 11m baselines
- 1 30m roll = 2 x 8.5m T-lines
1x 13m center service line
- 18 solid profiled steel tube plugs
- 18 high-grade steel profiled tubular anchor pegs
- 18 end fixers
- 1 Installation instructions